



WB Two Ram



For all recycling grades and Non-Ferrous metals



Key Features:

Stamper Option ~ *for enhanced automatic baling for difficult to shear materials*

Easy to operate controls

Optimal hydraulic operating pressures

Bellevue, Ohio
800-843-7512
www.americanbaler.com

WB Two Ram Series

PRODUCTION OPTIONS

Models: W721, W828
Bale Size: 60" x 30" x 45"
Feed Opening: 87" x 60",
110" x 60" (long side-no stamper)
Main Cylinder: 12" bore trunnion design
Main Ram Penetration: Deep penetration into
bale chamber
System Pressure: 3000 psi (W721),
3500 psi (W828)
Main Motor: Twin 50, Twin 75 HP,
or Triple 75 HP (Model W828 only)
Feed Type: Conveyor, loader
Wire Tying: Accent 470 standard;
Plastic strapping optional
Shear: Serrated blade standard
(straight blades optional)
Door: Combination bale release and bale
separation door

18.8 Ton Hydraulic Stamper1
Tool steel shear blades: straight ram/serrated
beam blades for MSW & NF metals applications
Open operator platform above charge box w/
stairs & railing
Operator platform and enclosure with heat & AC
W828: Upgrade to flooded inlet power unit
(T75HP) W828: Upgrade to flooded inlet power
unit (225HP)
Nema 4 upgrade
Power unit located other than position #1
Accent-Enviro Bale System
Plastic strapper in lieu of standard wire strapper
Power Unit Cover
Increased Cooling Capacity: Recommended for
ambient temperatures above 100 Degrees F,
Required for ambient temperatures above 110
Degrees F
Panel heaters both panels



Distributed By:



Phone: 205.648.7272 Fax: 205.648.7205
Email: sales@aafps.com

